



## 20K PLATFORM 15' x 38'



### DETAILED SPECIFICATIONS

LIFT SPEED	FPM 3' UP	FPM 2' DOWN
PLATFORM TRAVEL	15'	
DRAFT OF PLATFORM	14"	
CABLE SPECIFICATIONS	3/8" STAINLESS STEEL	
DECKING	EVERGRAIN COMPOSITE GRAY	
MOTOR / PUMPS	2HP / 1GPM	
POWER REQUIRED	208-230/ 240VAC 20 AMP BREAKER	

**CALL 1-800-688-1033**

### OVERALL DIMENSION

17' WIDE X 38' LONG

### MOVING PLATFORM

15' WIDE X 38' LONG

### PILES REQUIRED

6-12" DIAMETER

DIMENSIONS CAN BE ALTERED TO FIT YOUR PROJECT REQUIREMENTS.

### STANDARD EQUIPMENT

ALL ALUMINUM & STAINLESS  
 STAINLESS STEEL PULLEYS  
 STAINLESS STEEL FITTINGS  
 REMOTE CONTROL  
 HIDE-A-WAY HULL GUIDES  
 COMPOSITE DECKING  
 EPOXY COATED HYDRAULIC RAMS  
 PLUG AND PLAY CONTROL BOX  
 PLUG AND PLAY MOTORS  
 EASY ADJUST BUNK SYSTEM  
 POWDER COATED COVERS  
 COMPLETE WIRING KIT  
 2 YEAR BUMPER TO BUMPER WARRANTY